



MECHANICAL SPLICE & HEADED DEVICE OPTIONS COVERED BY EVALUATION REPORT

R1 13 APR 2026

MECHANICAL SPLICE SYSTEM		EVALUATION REPORT	SPLICE TYPE	ASTM A615, A706 GRADE 60		ASTM A615 GRADE 75		ASTM A615, A706 GRADE 80		
				TYPE 1	TYPE 2	TYPE 1	TYPE 2	TYPE 1	TYPE 2	
				125% <i>fy</i> A615, A706 Grade 60 75,000 psi	100% <i>fu</i> A615, A706 Grade 60 80,000 psi	125% <i>fy</i> A615 Grade 75 93,750 psi	100% <i>fu</i> A615 Grade 75 100,000 psi	125% <i>fy</i> A615, A706 Grade 80 100,000 psi	100% <i>fu</i> A615, A706 Grade 80 100,000 psi	
BPI® BARGRIP XL	SWAGED COUPLERS, INSTALLED BY FIELD PRESS	IAPMO UES ER-0796	STANDARD	✓	✓					
			TRANSITION	✓	✓					
BPI® BARSPLICER XP	THREADED STEEL COUPLERS, WITH BARSPLICE THREADED REBAR	IAPMO UES ER-0796	UNCOATED	✓	✓	✓	✓	✓	✓	
			EPOXY	✓	✓	✓	✓	✓	✓	
TAPER THREADED GRIP-TWIST®	TAPER THREADED COUPLERS, SHOP SWAGED BY BP2600 PRESS	IAPMO UES ER-0796	STANDARD	✓	✓					
			TRANSITION	✓	✓					
			POSITION	✓	✓					
ZAP SCREWLOK®	SHEAR SCREW COUPLERS, FIELD INSTALLED BY IMPACT WRENCH	IAPMO UES ER-0796	TYPE 2*	✓	✓					
			TRANSITION	✓	✓					
			FX			✓ #11, #14, #18	✓ #11, #14, #18	✓ #11, #14, #18	✓ #11, #14, #18	
HEADED DEVICE SYSTEM		EVALUATION REPORT	HEAD TYPE	CLASS A	CLASS HA	CLASS A	CLASS HA	CLASS A	CLASS HA	
				100% <i>fu</i> A615, A706 Grade 60 80,000 psi	100% <i>fu</i> A615, A706 Grade 60 80,000 psi	100% <i>fu</i> A615 Grade 75 100,000 psi	100% <i>fu</i> A615 Grade 75 100,000 psi	100% <i>fu</i> A615, A706 Grade 80 100,000 psi	100% <i>fu</i> A615, A706 Grade 80 100,000 psi	
				BUTTONHEAD™		IAPMO UES ER-0331	BNH (5Ab)	✓	✓	✓
ASTM A970 HEADED DEVICE, SHOP SWAGED BY BP2600 PRESS		BNX (10Ab)	✓	✓	✓		✓	✓	✓	
FITT® TERMINATION		ASTM A970 HEADED DEVICE, FIELD INSTALLED WITH PIPE WRENCHES	IAPMO UES ER-0331	5Ab	✓	✓	✓	✓	✓	✓
				10Ab	✓	✓	✓	✓	✓	✓

\* UNCOATED SIZES #4 - #18, EPOXY COATED OR GALVANIZED SIZES #4 - #11